

# CSE ROBUST SC 18

## Features

## Customer Benefit

### CSE ROBUST SC18



- |  |  |
|--|--|
| <ul style="list-style-type: none"> <li>• TRC Technology (Triple Rubber Compound)</li> <li>• SIT construction</li> <li>• Heat tolerant compound</li> <li>• Rectangular bead technology</li> <li>• ROBUST sidewall</li> <li>• Sidewall RTD line (Remaining Tread Depth)</li> </ul> | <ul style="list-style-type: none"> <li>➤ High mileage</li> <li>➤ Maintenance free</li> <li>➤ Comfortable ride</li> <li>➤ Lateral stability</li> <li>➤ Low mounting costs</li> <li>➤ High ambient temperature applications</li> <li>➤ High load, speed and duration service</li> <li>➤ Excellent rim fit</li> <li>➤ Damage resistant</li> <li>➤ Maintenance free</li> <li>➤ Consumer &amp; driver friendly</li> </ul> |
|--|--|

# CSE ROBUST SC 18

## Size Range

Tire		Article number	Rim	Tire dimensions (mm)		Tire load capacity (kg)													
Size	Base version			Standard value		Stationary	on other vehicles <sup>1)</sup> at max. speed (km/h)			on fork lifts max. 25 km/h									
	SIT/S			Width	Outer dia.		6	10	25	load <sup>4)</sup> wheel	Steered <sup>2)</sup> wheel								
acc. to ETRTO <sup>3)</sup>																			
8" Rim																			
5.00-8	S	1378460	3.00 D-8	143	476	1645	1415	1285	1090	1415	1090								
125/75-8 (15x41/2-8)	S	1377986		132	393	1210	1040	945	800	1040	800								
	SIT	1377987																	
180/70-8 (18x7-8)	S	1379780	4.33 R-8	187	471	2490	2145	1945	1650	2145	1650								
	SIT	1379781																	
9" Rim																			
6.00-9	S	1378674	4.00 E-9	173	551	2190	1885	1710	1450	1885	1450								
	SIT	1378675																	
10" Rim																			
6.50-10	S	1378771	5.00 F-10	191	600	2720	2340	2125	1800	2340	1800								
	SIT	1378772																	
225/75-10 (23x9-10)	S	1378181	6.50 F-10	243	607	4000	3445	3125	2650	3445	2650								
	SIT	1378182																	
200/50-10	S	1377360										221	467	2870	2470	2240	1900	2470	1900
	SIT	1377361																	
12" Rim																			
7.00-12	S	1378874	5.00 S-12	207	685	3380	2920	2645	2240	2920	2240								
	SIT	1378875																	
250/75-12 (27x10-12)	S	1378384	8.00 G-12	275	704	4530	3900	3540	3000	3900	3000								
	SIT	1378385																	
15" Rim																			
8.25-15	S	1379170	6.5-15	253	853	5510	4750	4300	3650	4750	3650								
	SIT	1379171																	
225/75-15 (28x9-15/ 8.15-15)	S	1376984	7.0-15	233	721	4380	3900	3540	3000	3900	3000								
	SIT	1376985																	
250/70-15 (250-15)	S	1379288	7.0-15	265	750	5510	4750	4300	3650	4750	3650								
	SIT	1379289																	
	S	1379290	7.5-15	270															
315/70-15 (3300-15)	S	1379382	8.0-15	324	857	6795	5850	5310	4500	5850	4500								
	SIT	1379383																	
20" Rim																			
10.00-20	S	1379590	7.5-20	297	1088	7550	6000	5450	5000	6000	5000								
	S	1379588	8.0-20	302	1088	7550	6000	5450	5000	6000	5000								