



# T-900

BIAS PNEUMATIC - MAXIMUM INTENSITY APPLICATIONS

### Main Benefits

- **Block tread design**  
Large footprint lowers stress and maximizes tire life.
- **Sidewall protection**  
Reinforced sidewall to avoid impact damage.
- **Enhanced stability**  
Faster load positioning and cornering.
- **Wear resistant technology**  
Maximum lifetime, reduced downtime, increasing value.
- **Energy management system**  
Keeps the internal temperature low ensuring maximum uptime.
- **Shock absorbance**  
Tire absorbs shock from obstacles.
- **Rim security**  
Rim protection from accidental damage and anti slip bead wires.

### Polymer Engineering, Application Expertise

As part of our premium range this product is capable of performing in demanding applications to deliver high performance in key areas.



TIRE LIFE



PUNCTURE RESISTANCE



COOL RUNNING



STABILITY

# T-900

BIAS PNEUMATIC - MAXIMUM INTENSITY APPLICATIONS

TREAD PATTERNS



T-900

Size	Alternative Size	Ply Rating	Rim	Product Dimensions [mm]			Minimal Dual Spacing [mm]	Inflation Pressure [bar]	Tire Type	Load Index	Speed Symbol	Load Capacity [kg]	
				Overall Diameter	Section Width	Tread Depth						Counterbalanced Lift Trucks up to 25 km/h	
												Load Wheel	Steering Wheel
5.00-8		10	3.00D-8	468	140	13	158	10.00	Tube Type	111	A5	1,415	1,090
18x7-8	180/70-8	16	4.33R-8	462	168	16	199	10.00	Tube Type	125	A5	2,145	1,650
6.00-9		12	4.00E-9	543	160	15	192	10.00	Tube Type	121	A5	1,885	1,450
23x9-10	225/75-10	20	6.50F-10	585	230	19	259	10.00	Tube Type	142	A5	3,445	2,650
6.50-10		12	5.00F-10	590	182	18	212	9.00	Tube Type	125	A5	2,145	1,650
23x10-12	250/60-12	20	8.00G-12	600	245	22	293	10.00	Tube Type	145	A5	3,770	2,900
7.00-12		14	5.00S-12	680	191	18	230	9.00	Tube Type	134	A5	2,755	2,120
7.00-12		16	5.00S-12	680	191	18	230	10.00	Tube Type	136	A5	2,910	2,240
27x10-12	250/75-12	16	8.00G-12	685	250	22	293	8.00	Tube Type	146	A5	3,900	3,000
27x10-12	250/75-12	24	8.00G-12	685	250	22	293	10.40	Tube Type	155	A5	5,040	3,875
28x9-15	225/75-15 (8.15-15)	14	7.0-15	710	230	18	248	10.00	Tube Type	146	A5	3,900	3,000
250-15	250/70-15	20	7.0-15	742	240	19	282	10.00	Tube Type	155	A5	5,040	3,875
7.00-15	29x8-15	14	5.5-15	760	204	20	236	8.80	Tube Type	140	A5	3,275	2,520
7.50-15		16	6.0-15	778	215	21	254	10.00	Tube Type	146	A5	3,900	3,000
7.50-16	250/80-16	12	6.00G-16	805	220	21	254	8.00	Tube Type	144	A5	3,630	2,790
300-15	315/70-15	20	8.0-15	840	290	23	345	9.00	Tube Type	164	A5	6,500	5,000
8.25-15		14	6.5-15	841	247	19	281	8.00	Tube Type	149	A5	4,225	3,250
8.25-15		16	6.5-15	841	247	19	281	9.30	Tube Type	152	A5	4,615	3,550
355/65-15	32x12½-15 (350-15)	24	9.75-15	843	334	29	407	10.00	Tube Type	170	A5	7,800	6,000
355/65-15	32x12½-15 (350-15)	32*	9.75-15	843	334	29	407	12.50	Tube Type	177	A5	9,490	7,300
9.00-20	270/95-20	14	7.0-20	1,015	265	27	311	9.00	Tube Type	160	A5	5,850	4,500
10.00-20	290/95-20	16	7.5-20	1,085	294	32	334	9.00	Tube Type	164	A5	6,500	5,000
11.00-20	300/95-20	18	8.0-20	1,110	302	33	352	10.00	Tube Type	170	A5	7,800	6,000
12.00-20	330/95-20	20	8.0-20	1,145	325	35	372	10.00	Tube Type	175	A5	8,970	6,900
12.00-20	330/95-20	24	8.0-20	1,145	325	35	372	10.40	Tube Type	178	A5	9,710	7,470
12.00-20	330/95-20	28	8.0-20	1,145	325	35	372	10.90	Tube Type	180	A5	10,400	8,000
12.00-24	330/95-24	20	8.5-24	1,245	320	35	378	10.00	Tube Type	178	A5	9,750	7,500
12.00-24	330/95-24	24	8.5-24	1,245	320	35	378	10.40	Tube Type	178	A5	9,945	7,650
14.00-24	385/95-24	24	10.00W-24	1,360	380	39	450	10.00	Tube Type	186	A5	12,350	9,500
14.00-24	385/95-24	24*	10.00W-24	1,360	380	39	450	10.00	Tubeless	186	A5	12,350	9,500
14.00-24	385/95-24	28	10.00W-24	1,360	380	39	450	10.40	Tube Type	186	A5	12,600	9,690

\* Requires special rim & components, please check with your local Trelleborg representative



Trelleborg Wheel Systems Italia S.p.A.  
Via Nazionale Tiburtina, 143 - 00010 Villa Adriana (RM) Italy  
Phone: +39 0774 384701 - Fax: +39 0774 384702  
www.trelleborg.com/wheels



facebook.com/Trelleborgmaterialhandling

Download the App for free



Tire iBrochure