

# Y520

**INDUSTRIAL, FORKLIFT**  
**INDUSTRIEL, POUR CHARIOT ÉLEVATEUR**



## LONG SERVICE LIFE

The Y520 has been specially designed for forklift applications. This tire provides long service life with deep tread and large ground contact area.

### FEATURES AND BENEFITS

- Long wearing deep tread and good puncture resistance.
- Also available in steel breaker construction for maximum puncture resistance.

## LONGUE DURÉE DE VIE

Le pneu Y520 a été spécialement conçu pour les chariots élévateurs. Il procure d'innombrables heures de service grâce à sa semelle profonde et à sa large surface de contact.

### CARACTÉRISTIQUES ET AVANTAGES

- D'usure lente, il offre une bonne résistance aux crevaisons.
- Ce pneu est également offert en version ultra résistante aux crevaisons grâce à des nappes sommet métalliques.

All tube-type truck tires are supplied from Yokohama Tire as a set (tire and tube).

Tous les pneus pour camions avec chambre, sont fournis par Pneus Yokohama en ensemble (pneu et chambre).



# INDUSTRIAL TIRE PNEU INDUSTRIEL

Description	Part No. No. d'article	Std. Weight (lbs) Poids Std (lb)	Rim Widths (inches) Largeurs de jantes (po)		Inflated Dimensions (inches) Dimensions pneu gonflé (po)		Max. Load (lbs) @ Max. PSI Charge maximale en lb/po				Max. Inflation Pressure (PSI) Charge maximale en lb/po	Tread Depth 1/32" Profondeur de sculpture (1/32e po)	
			Pref.	Alt	Overall Width Largeur hors tout	Overall Diameter Diamètre hors tout	Load Wheels Roues porteuses		Steering Wheels Roues directrices				
							Max. 10 M/H	Max. 15 M/H	Max. 15 M/H	Max. 20 M/H			
8"	500-8 8D ID TT	130152007	15.43	3.50	3.00	5.6	18.6	N/A	N/A	1830	1605	115	19
9"	600-9 10E ID TT	130152011	25.09	4.00	0.00	6.3	21.2	3715	3340	2820	2480	125	24
10"	650-10 10E ID TT	130152009	30.08	5.00	0.00	6.9	23.1	4225	3805	3210	2825	N/A	25
12"	700-12 12F ID TT	130152012	44.83	5.00	0.00	7.5	27.0	5995	5395	4555	4005	125	26
15"	300-15 18J ID TT	130152017	117.12	8.00	8.00	11.8	33.2	14320	13005	10010	9180	115	30
	550-15 8D ID TT	120152004	29.62	4.50	0.00	6.0	26.7	4730	4300	3185	2955	105	22
	700-15 12F ID TT	130152013	50.59	5.50	0.00	7.7	29.7	6940	6245	5275	4635	125	26
	825-15 14G ID TT	130152015	83.10	6.50	0.00	9.3	33.8	9385	8445	7325	6270	120	27
	28X9-15 12F ID TT	120152003	69.44	7.00	0.00	8.8	28.2	6880	6190	5230	4595	120	23
<b>STEEL BREAKER / NAPPE-SOMMET EN ACIER</b>													
8"	500-8 8D SB ID TT	130152008	17.43	3.50	3.00	5.6	18.6	N/A	N/A	1830	1605	115	19
9"	600-9 10E SB ID TT	130152005	27.91	4.00	0.00	6.3	12.2	3715	3340	2820	2480	125	24
10"	650-10 10E SB ID TT	130152010	33.10	5.00	0.00	6.9	23.1	4225	3805	3210	2825	115	25
12"	700-12 12F SB ID TT	130152006	47.94	5.00	0.00	7.5	27.0	5995	5395	4555	4005	125	26

Technical specifications subject to change without notice. / Ces données techniques peuvent être modifiées sans aucun préavis.

