

Tire Size	LOAD INDX/SPEED RTG	Ply Rating	TYPE	Tread Depth	Overall Diameter	Section Width	RIM WIDTH	Max Load @PSI	AOT Item
18x7-8	-	16	T/T	16.9	18.3	6.6	4.33	3615@145	DS6001
21x8-9	-	14	T/T	23.2	21	8	6.00	4660@145	DS9819
4.00-8	-	8	T/T	17.5	16.3	4.5	3.25	1477@130	DS8867
5.00-8	-	8	T/T	16	18.5	5.2	3.00	1830@115	DS6019
6.90/6.00-9	-	10	T/T	17.9	21.5	6.3	4.00	3340@125	DS6015
6.50-10	-	10	T/T	19.9	23.5	7	5.00	3805@115	DS6020
7.50-10	-	12	T/T	22.9	25.5	8	5.5	5090@120	DS6021
7.00-12	-	12	T/T	22.9	26.9	7.6	5.00	5395@125	DS6025
7.00-12	-	14	T/T	22.9	26.9	7.6	5.00	5885@145	DS6026
7.00L-15	-	12	T/T	22.9	28.8	7.8	5.5	6185@125	DS6031
7.00-15	-	12	T/T	22.9	30	8	6.00	6245@125	DS6030
7.50-15 [30"]	-	12	T/T	22.9	30	8	6.00	6245@125	DS6035
7.50-15 [30"]	-	14	T/T	22.9	30	8	6.00	7725@140	DS6037
7.50-15 [32"]	-	12	T/T	22.9	31.8	8.5	6.00	6920@115	DS6036
8.15-15	-	12	T/T	24.9	27.8	8.7	7.00	6190@120	DS6040
8.15-15	-	14	T/T	24.9	27.8	8.7	7.00	6775@140	DS6041
8.25-15	-	12	T/T	22.9	33.3	9.3	6.5	7810@105	DS6045
8.25-15	-	14	T/T	22.9	33.3	9.3	6.5	8445@120	DS6046
250-15	-	18	T/T	24.6	28.9	9.8	7.5	9050@150	DS6048
300-15	-	20	T/T	26.1	33.1	11.8	8.00	13100@135	DS6049