



STRONG SHOULDERS FOR YOUR BUSINESS.

GENERAL TIRE PRESS-ON-BANDS

SINCE 1915.
GENERAL TIRE. A BRAND OF CONTINENTAL.

GENERAL TIRE ™

WWW.GENERALTIRE.COM





PRESS-ON-BANDS A STABLE BASIS.

With over 100 years of experience, General Tire develops tires to get the job done right. Our new press-on-band range is no different. General Tire press-on-bands have excellent resistance to cuts and tears, provide high mileage and durability, and deliver a great price performance ratio.

Every day, General Tire press-on-bands will prove their superior traction, impressive tilt stability, and outstanding maneuverability when you need it most.

GENERAL TIRE TRAC

OPTIMIZED FOR MATERIAL HANDLING.



TECHNICAL DATA

FORK LIFT TRUCKS

Stock Code	Dimensions		Max. Speed 6 mph (10 km/h)				10 mph (16 km/h)			
			Load wheel		Steering wheel		Load wheel		Steering wheel	
	Inch	mm	lbs	kg	lbs	kg	lbs	kg	lbs	kg
13003180000	16X6X10 1/2	406/152-267	4222	1915	3461	1570	3770	1710	3164	1435
13003200000	18X6X12 1/8	457/152-308	4619	2095	3792	1720	4123	1870	3472	1575
13003220000	18X7X12 1/8	457/178-308	5622	2550	4619	2095	5027	2280	4222	1915
13003240000	21X7X15	533/178-381	6327	2870	5192	2355	5644	2560	4740	2150
13003260000	21X8X15	533/203-381	7463	3385	6129	2780	6658	3020	5589	2535
13003290000	22X9X16	559/229-406	8896	4035	7308	3315	7948	3605	6669	3025

FEATURES & BENEFITS



OPTIMIZED TREAD DESIGN ENSURES BEST TRACTION AND HIGH STABILITY.



EXCELLENT MILEAGE DUE TO WEAR RESISTANT COMPOUND.

TECHNICAL DATA

OTHER VEHICLES

Stock Code	Dimensions		Max. Speed					
			4 mph (6 km/h)		6 mph (10 km/h)		10 mph (16 km/h)	
	Inch	mm	lbs	kg	lbs	kg	lbs	kg
13003180000	16X6X10 1/2	406/152-267	4222	1915	3461	1570	3164	1435
13003200000	18X6X12 1/8	457/152-308	4619	2095	3792	1720	3472	1575
13003220000	18X7X12 1/8	457/178-308	5622	2550	4619	2095	4222	1915
13003240000	21X7X15	533/178-381	6327	2870	5192	2355	4740	2150
13003260000	21X8X15	533/203-381	7463	3385	6129	2780	5589	2535
13003290000	22X9X16	559/229-406	8896	4035	7308	3315	6669	3025

GENERAL TIRE SMOOTH

OPTIMIZED FOR MATERIAL HANDLING.



TECHNICAL DATA

FORK LIFT TRUCKS

Stock Code	Dimensions		Max. Speed 6 mph (10 km/h)				10 mph (16 km/h)			
			Load wheel		Steering wheel		Load wheel		Steering wheel	
	Inch	mm	lbs	kg	lbs	kg	lbs	kg	lbs	kg
13003110000	10X5X6 1/2	254/127-165	2227	1010	1830	830	1995	905	1676	760
13003120000	14X4 1/2X8	356/114-203	2579	1170	2116	960	2304	1045	1929	875
13003130000	15X5X11 1/4	381/127-286	3064	1390	2524	1145	2734	1240	2304	1045
13003140000	16 1/4X5X11 1/4	413/127-286	3362	1525	2756	1250	2998	1360	2524	1145
13003150000	16 1/4X6X11 1/4	413/152-286	4233	1920	3472	1575	3781	1715	3175	1440
13003160000	16X5X10 1/2	406/127-267	3329	1510	2734	1240	2965	1345	2491	1130
13003170000	16X6X10 1/2	406/152-267	4222	1915	3461	1570	3770	1710	3164	1435
13003190000	18X6X12 1/8	457/152-308	4619	2095	3792	1720	4123	1870	3472	1575
13003210000	18X7X12 1/8	457/178-308	5622	2550	4619	2095	5027	2280	4222	1915
13003230000	21X7X15	533/178-381	6327	2870	5192	2355	5644	2560	4740	2150
13003250000	21X8X15	533/203-381	7463	3385	6129	2780	6658	3020	5589	2535
13003270000	22X8X16	559/203-406	7727	3505	6349	2880	6900	3130	5787	2625
13003280000	22X9X16	559/229-406	8896	4035	7308	3315	7948	3605	6669	3025

FEATURES & BENEFITS



SMOOTH TREAD FOR HIGH TILTING STABILITY AND REDUCED TREAD CHUNKING.



SPECIAL COMPOUND PROVIDES EXCELLENT DENSITY FOR HIGH MILEAGE.

TECHNICAL DATA

OTHER VEHICLES

Stock Code	Dimensions		Max. Speed					
	Inch	mm	4 mph (6 km/h)		6 mph (10 km/h)		10 mph (16 km/h)	
			lbs	kg	lbs	kg	lbs	kg
13003110000	10X5X6 1/2	254/127-165	2227	1010	1830	830	1676	760
13003120000	14X4 1/2X8	356/114-203	2579	1170	2116	960	1929	875
13003130000	15X5X11 1/4	381/127-286	3064	1390	2524	1145	2304	1045
13003140000	16 1/4X5X11 1/4	413/127-286	3362	1525	2756	1250	2524	1145
13003150000	16 1/4X6X11 1/4	413/152-286	4233	1920	3472	1575	3175	1440
13003160000	16X5X10 1/2	406/127-267	3329	1510	2734	1240	2491	1130
13003170000	16X6X10 1/2	406/152-267	4222	1915	3461	1570	3164	1435
13003190000	18X6X12 1/8	457/152-308	4619	2095	3792	1720	3472	1575
13003210000	18X7X12 1/8	457/178-308	5622	2550	4619	2095	4222	1915
13003230000	21X7X15	533/178-381	6327	2870	5192	2355	4740	2150
13003250000	21X8X15	533/203-381	7463	3385	6129	2780	5589	2535
13003270000	22X8X16	559/203-406	7727	3505	6349	2880	5787	2625
13003280000	22X9X16	559/229-406	8896	4035	7308	3315	6669	3025

Continental Reifen Deutschland
Commercial Specialty Tires
Büttnerstraße 25
D-30165 Hannover

T. +49 511 938-01
mail_service@conti.de
www.generaltire.com

GENERAL TIRE  TM