



## 16.9 - 24 12 TG-01 TL

- Robust industrial pattern with higher resistance to puncture and tread wear.

### TECHNICAL DATA

<b>Tyre size</b>	16.9 - 24	<b>Tread Pattern</b>	TG-01
<b>Tyre size alternative</b>	-	<b>Ply rating</b>	12
<b>Service description LI/SS</b>	149 A6	<b>Type</b>	TL
<b>Permitted Rims</b>	W 15Lx24 W 14Lx24	<b>Tube</b>	-
<b>Overall diameter - new tyre (in)</b>	51.6	<b>Section width - new tyre (in)</b>	16.9
<b>Overall diameter - max. in service (in)</b>	53.3	<b>Overall width - max. in service (in)</b>	18.2
<b>Rolling Circumference (in)</b>	150	<b>Loaded Static Radius (in)</b>	22.8
<b>Tread depth (32nd)</b>	31	<b>EAN code</b>	8590341039729

### LOAD CAPACITY PER TYRE

Tyre load at pressure (PSI)				Speed (mph)
33	35	36	38	-
14,531	14,961	15,391	15,843	0 Static
7,894	8,125	8,368	8,611	6
9,470	9,757	10,044	10,330	6 cyclic
6,880	7,089	7,299	7,508	12
6,571	6,769	6,968	7,166	19
6,317	6,505	6,692	6,891	25
5,744	5,920	6,086	6,262	31