



## 19.5L - 24 IND 12 GRIP-n-RIDE TL

Tread pattern suitable for backhoe loaders and other types of loaders with excellent self-cleaning properties and reinforced sidewall.

[Multipurpose Tires Leporello](#)

### TECHNICAL DATA

Tire size	19.5L - 24 IND	Tread Pattern	GRIP-n-RIDE
Alternative tire size	-	Ply rating	12
Service description LI SS	151 A8	Tubeless / Tube Type	TL
Permitted rims	W16Lx24 DW16Lx24	Tube	-
Overall diameter - new tire (in)	51.7	Section width - new tire (in)	19.5
Overall diameter - max. in service (in)	53.4	Overall width - max. in service (in)	21.1
Rolling circumference (in)	152	Loaded static radius (in)	24
Tread Pattern Depth (32nd)	34	Tire weight (lbs)	188.5
EAN code	8590341066046		

### PRESSURE TABLE

Tire load at pressure (PSI)							Speed (mph)
16	19	22	25	28	30	33	-
9,945	11,234	12,524	13,825	15,600	16,560	17,497	0 Static
5,402	6,108	6,813	7,508	8,478	8,996	9,515	6
6,483	7,332	8,170	9,018	10,176	10,805	11,411	6 cyclic
4,719	5,325	5,931	6,549	7,387	7,850	8,291	12
4,498	5,083	5,667	6,251	7,056	7,486	7,916	19
4,322	4,884	5,446	6,009	6,780	7,199	7,607	25
3,936	4,443	4,961	5,468	6,174	6,549	6,924	31