


# FERENTINO FORZA POB

## FERENTINO FORZA POB

## FERENTINO FORZA POB NON MARKING



**NM**  
non marking

Optimal crowned profile

- Excellent cushioning for improved comfort

High-performance natural rubber compound

- Reduces chunking and cutting Suitable for both IC and electric trucks

Perfect bonding

- High quality bonding technology is used to keep the layers intact while working with heavy loads.

NMW - NON MARKING WHITE  
NMG - NON MARKING GRAY  
NMY - NON MARKING YELLOW  
■ - AVAILABLE SHORTLY

**FERENTINO**  
TYRE CORPORATION

# TECHNICAL DATA

TYRE SIZE D W do (pollici)	PROFILE	TYRE SIZE D W do (mm)	WEIGHT (kg)	LOAD CAPACITY (kg) FOR VEHICLES AT THE MAX SPEEDS OF								LOAD CAPACITY FOR VEHICLES	
				10 km/h		16 km/h		25 km/h		MANUAL TRACTION	MAX SPEED (16 km/h)		
				CARRYING WHEEL	STEERING WHEEL	CARRYING WHEEL	STEERING WHEEL	CARRYING WHEEL	STEERING WHEEL				
10x4x6½	SM	254x102x165,1	NEW	5,8	780	640	695	585	565	465	-	555	
10x5x6½	SM	254x127x165,1		7,2	1015	835	905	765	735	605	-	725	
10x5x6½	TR	254x127x165,1	NEW	7	1015	835	905	765	735	605	-	725	
12x4½x8	SM	305x114x203,2		9	1045	855	935	785	760	625	-	745	
14x4½x8	SM	356x114x203,2		11,3	1165	960	1045	875	845	695	-	835	
14x5x10	SM	356x127x254		11,5	1335	1095	1195	1000	970	795	-	-	
16x5x10½	SM	406x127x266,7		14,8	1510	1240	1345	1130	1095	900	-	1080	
16x5x10½	TR	406x127x266,7	NEW	14,5	1510	1240	1345	1130	1095	900	-	1080	
16x6x10½	SM	406x152x266,7		17,7	1905	1565	1705	1430	1385	1135	-	1365	
16x6x10½	TR	406x152x266,7	NEW	17,3	1905	1565	1705	1430	1385	1135	-	1365	
16x7x10½	SM	406x178x266,7		20,7	2325	1910	2070	1740	1685	1380	-	-	
15x5x11¼	SM	381x127x285,8		12,1	1395	1145	1245	1045	1015	830	-	995	
15x6x11¼	SM	381x152x285,8		14,5	1720	1415	1535	1290	1250	1025	-	1230	
16¼x5x11¼	SM	413x127x285,8	NEW	14	1525	1255	1365	1145	1110	910	-	1090	
16¼x6x11¼	SM	413x152x285,8		17,3	1915	1575	1710	1435	1395	1140	-	1370	
16¼x6x11¼	TR	413x152x285,8	NEW	17	1915	1575	1710	1435	1395	1140	-	1370	
16¼x7x11¼	SM	413x178x285,8		20,3	2320	1905	2075	1740	1685	1385	-	1660	
18x6x121/8	SM	457x152x308		20,6	2100	1720	1870	1575	1525	1250	-	1500	
18x6x121/8	TR	457x152x308		20,2	2100	1720	1870	1575	1525	1250	-	1500	
18x7x121/8	SM	457x178x308		24,6	2550	2100	2280	1910	1855	1520	-	1825	
18x7x121/8	TR	457x178x308	NEW	24,1	2550	2100	2280	1910	1855	1520	-	1825	
18x8x121/8	SM	457x203x308		28,2	3000	2475	2680	2255	2180	1790	-	2150	
18x8x121/8	TR	457x203x308	NEW	27,8	3000	2475	2680	2255	2180	1790	-	2150	
21x7x15	SM	533x178x381		30,1	2875	2350	2560	2150	2085	1710	-	2050	
21x7x15	TR	533x178x381		29,4	2875	2350	2560	2150	2085	1710	-	2050	
21x8x15	SM	533x203x381		34,6	3375	2775	3025	2540	2455	2015	-	2425	
21x8x15	TR	533x203x381		34	3375	2775	3025	2540	2455	2015	-	2425	
20x8x16	SM	508x203x406,4		34	3010	2470	2685	2255	2185	1790	-	-	
22x8x16	SM	559x203x406,4		38,3	3500	2875	3130	2625	2545	2085	-	2500	
22x9x16	SM	559x229x406,4		40,2	4050	3325	3600	3025	2930	2400	-	2895	
22x9x16	TR	559x229x406,4	NEW	39,4	4050	3325	3600	3025	2930	2400	-	2895	
22x12x16	SM	559x305x406,4		54	5625	4625	5030	4225	4090	3350	-	4025	
22x12x16	TR	559x305x406,4	NEW	53	5625	4625	5030	4225	4090	3350	-	4025	
28x12x22	SM	711x305x559		74,6	6740	5540	6020	5060	4900	4015	-	4820	