



MID-RANGE MATERIALS HANDLING PRESS ON SOLID  
**MPC2**

**Multi-purpose tire**

Features & Benefits:

- High quality, 100% natural rubber compound
- Soft riding compounds provide excellent shock absorption
- Available in multi-purpose and non-marking compounds
- Wide and flat profile delivers exceptional stability
- Traction version features an aggressive tread design to provide exceptional grip



# MPC2

## TECHNICAL SPECIFICATIONS

### SMOOTH

Tire Size	Load Capacity (lbs)		Weight Standard (lbs)	Weight Non Marking (lbs)
	Forklift trucks up to 6 mph	Forklift trucks up to 10 mph		
14x4½x8	2,390	2,120	23	23
16x5x10½	3,090	2,730	33	33
16x6x10½	3,920	3,460	35	36
15x5x11¼	2,850	2,520	28	28
16¼x5x11¼	3,120	2,760	27	27
16¼x6x11¼	3,930	3,480	36	40
18x6x12½/8	4,290	3,800	44	44
18x7x12½/8	5,220	4,620	50	50
18x8x12½/8	6,150	5,440	58	58
21x7x15	5,870	5,200	64	64
21x8x15	6,930	6,130	75	75
22x8x16	7,170	6,340	82	82
22x9x16	8,260	7,310	92	92
22x12x16	11,530	10,200	123	127


### TRACTION

Tire Size	Load Capacity (lbs)		Weight Standard (lbs)	Weight Non Marking (lbs)
	Forklift trucks up to 6 mph	Forklift trucks up to 10 mph		
16x6x10½	3,920	3,460	37	37
16¼x6x11¼	3,930	3,480	36	36
18x6x12½/8	4,290	3,800	44	44
18x7x12½/8	5,220	4,620	53	53
18x8x12½/8	6,150	5,440	59	59
21x7x15	5,870	5,200	62	62
21x8x15	6,930	6,130	71	71
22x8x16	7,170	6,340	76	75
22x9x16	8,260	7,310	84	84

### SPECIAL COMPOUNDS AVAILABLE



### TREAD PATTERNS



WWW.TRELLEBORG.COM/WHEELS